



MATERIAL SAFETY DATA SHEET

Product name:	GulfSea Diesel GF	Page:	1/4
Revision Date:	14/02/2017	Revision nr:	3
Product No.:	1DD2417	Supersedes:	25/07/2014

1. Identification of the product and the company

Trade name	:	GulfSea Diesel GF (SAE 40)
Use	:	Railroad engine oil
Company identification	:	Gulf Oil Marine Ltd. 13th Floor, Fortis Tower, No. 77-79 Gloucester Road, Wan Chai, Hong Kong Tel : (852) 3693 0568 Fax : (852) 3748 9960 www.gulf-marine.com
Emergency phone nr Company	:	Tel : (852) 3693 0568 As above

2. Information on ingredients

This product is not considered to be hazardous and contains hazardous components.

Substance name	Value (s)	CAS nr	EINECS nr	EC index	CERTIFICATE
Polyolefin polyamine succinimide polyol	: < 2.2 %	----	----	----	R53
HOB Calcium branched chain alkyl phenate sulphide	: < 3.5 %	----	291-829-9	----	R53
Calcium long chain alkaryl sulphonate	: < 0.7%	----	----	----	R43 R53
Branched alkylphenol and Calcium branched alkylphenol	: < 0.4%	----	----	----	R62 Xi; R38 N; R50-53
Calcium branched chain alkyl phenate, Mannich	: < 1.2%	----	----	----	R43

3. Hazards identification

Main hazards	:	Classified as a dangerous preparation according to Directive 1999/45/EC.
Adverse human health effects	:	May cause sensitization by skin contact.
Environmental hazards	:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Note	:	May produce an allergic reaction.

4. First aid measures

First aid	:	
– Inhalation	:	Assure fresh air breathing. Obtain medical attention if breathing difficulty persists.
– Skin contact	:	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical attention if irritation develops.
– Eye contact	:	Rinse immediately with plenty of water. Seek medical attention if irritation develops.
– Ingestion	:	DO NOT INDUCE VOMITING. Seek medical attention immediately.
Note to physician	:	If there is any suspicion of aspiration into the lungs either directly or as a result of vomiting, obtain medical advice.

5. Fire - fighting measures

Extinguishing media	:	
Suitable extinguishers	:	Water fog. Carbon dioxide. Dry chemical. Foam. Sand.
Extinguishers not to be used	:	Do not use a heavy water stream.
Surrounding fires	:	Use water spray or fog for cooling exposed containers.
Special exposure hazards	:	None under normal conditions.
Protection against fire	:	Do not enter fire area without proper protective equipment, including respiratory protection.



MATERIAL SAFETY DATA SHEET

Product name:	GulfSea Diesel GF	Page:	2/4
Revision Date:	14/02/2017	Revision nr:	3
Product No.:	1DD2417	Supersedes:	25/07/2014

Special procedures : None Identified.

6. Accidental release measures

- Personal precautions** : Keep public away from danger area. Wear recommended personal protective equipment. Equip cleanup crew with proper protection.
- Environmental precautions** : Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.
- After spillage and/or leakage** : Clean up any spills as soon as possible, using an absorbent material to collect it.
Collect spills and put it into appropriated container. Use suitable disposal containers. Recover the cleaning water for disposal. Spill area may be slippery.
- On soil** : May require excavation of contaminated soil.

7. Handling and storage

- General** : No naked lights. No smoking. Keep away from sources of ignition.
- Precautions in handling and storage** : Handle in accordance with good industrial hygiene and safety procedures.
- Storage** : Keep container closed when not in use. Keep only in the original container in a cool, well ventilated place. Keep at temperature not exceeding 45°C.
- Handling** : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

8. Exposure controls / personal protection

- Personal protection**
- **Respiratory protection** : No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.
 - **Hand protection** : Use neoprene or rubber gloves.
 - **Skin protection** : No special clothing/skin protection equipment is recommended under normal conditions of use.
 - **Eye protection** : Safety glasses.
- Industrial hygiene** : Provide local exhaust or general room ventilation to minimize dust and/or vapour concentrations. When using, do not eat, drink or smoke. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Occupational Exposure Limits** : According to TWA (TLV) ACGIH : 3 mg/m³ for oil mist.

9. Physical and chemical properties

- Physical state** : Liquid
- Colour** : Amber
- Odour** : Mild.
- Pour point [°C]** : -18
- Viscosity at 100°C [mm²/s]** : 15.6
- Flash point [°C] (ASTM D 92)** : 246
- Specific gravity** : 0.903

10. Stability and reactivity

- Physico-chemical stability** : Stable.
- Conditions to avoid** : Open flame. Sparks. Overheating.
- Materials to avoid** : Oxidizing agents. Strong acids, bases.
- Hazardous decomposition products** : Carbon dioxide. Carbon monoxide. Hydrogen sulfide.
- Hazardous reactions** : None under normal conditions.
- Hazardous Polymerization** : Will not occur.



MATERIAL SAFETY DATA SHEET

Product name:	GulfSea Diesel GF	Page:	3/4
Revision Date:	14/02/2017	Revision nr:	3
Product No.:	1DD2417	Supersedes:	25/07/2014

11. Toxicological information

Acute toxicity	:	Not expected to be toxic.
Inhalation	:	Practically non toxic at normal conditions of usage. May cause respiratory irritation following prolonged or repeated inhalation of excessive oil mist and vapours.
Dermal	:	Not expected to be a primary skin irritant. Prolonged or repeated exposure may lead to dermatitis.
Ingestion	:	Practically non toxic if swallowed in small doses. Larger quantities may cause nausea & diarrhoea.
Sensitization	:	May cause a sensitization.
Carcinogenicity	:	No data available.
Mutagenicity	:	Not expected to be a mutagenic hazard.

12. Ecological information

Ecological effects information	:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Bioaccumulative potential	:	Not determined.
Mobility soil	:	Ground water contamination may be caused through spillages.

13. Disposal considerations

Disposal	:	Dispose in a safe manner in accordance with local/national regulations.
-----------------	---	---

14. Transport information

General information	:	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
UN No.	:	Not regulated
ADR/RID	:	Not regulated
IMO-IMDG code	:	Not regulated
ICAO/IATA	:	Not regulated

15. Regulatory information

Symbol(s)	:	Irritant.
R Phrase(s)	:	R43 : May cause sensitization by skin contact. R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S Phrase(s)	:	S2 : Keep out of the reach of children. S37 : Wear suitable gloves. S46 : If swallowed seek medical advice immediately and show this container or label.
Additional phrase(s)	:	Contains : - Calcium branched chain alkyl phenate, Mannich - Calcium long chain alkaryl sulphonate. May produce an allergic reaction.



MATERIAL SAFETY DATA SHEET

Product name:	GulfSea Diesel GF	Page:	4/4
Revision Date:	14/02/2017	Revision nr:	3
Product No.:	1DD2417	Supersedes:	25/07/2014

16. Other information

- R-phrases listed in chapter 2**
- : R38 : Irritating to skin.
 - : R43 : May cause sensitization by skin contact.
 - : R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - : R53 : May cause long-term adverse effects in the aquatic environment.
 - : R62 : Possible risk of impaired fertility.
- Product information**
- : For specific or detailed technical data for this product, please contact your local sales representative.
- Note**
- : To the best of our knowledge and belief, the information and recommendations provided in this MSDS are correct. We make no warranty whatsoever, expressed or implied of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. We do not assume any liability for consequences of the uses of this information since it may be applied under conditions beyond our control or knowledge. The information is furnished on the condition that the recipients shall make their own decision as to safety and suitability of the material for their purposes. We will not be responsible for damages of any nature resulting from the use or reliance upon the information and recommendations. If you have purchased this product for supply to a third party, it is your duty to pass on to that third party the information given in this Data Sheet. If the third party is not an employer it is his duty to pass the information given in the Data Sheet to the employer of whoever uses or handles this product. It is an employer's duty to advise and instruct his employees handling this product (and others who may be affected), of any hazards described in the Data Sheet and of any precautions which should be taken to ensure safe handling of the product.

The contents and format of this MSDS are in accordance with EEC Commission Directive 93/112/EEC.

DISCLAIMER OF LIABILITY

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document