



Marine

# SAFETY DATA SHEET

Product name: GulfSea Power MDO 3012, 4012 Page: 1/8  
Supersedes date: 2019-11-18 Revision: 2019-11-18  
Product No.: SDS-ID: HK-EN/1.0

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name: GulfSea Power MDO 3012, 4012  
Container size: -

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Marine trunk piston engine oil.

### 1.3. Details of the supplier of the safety data sheet

Supplier: Gulf Oil Marine Ltd.  
28/F, Unit 2802 Citicorp Centre,  
18 Whitfield Road,  
Causeway Bay,  
Hong Kong  
Tel: +852 36930568  
Fax: +852 37489960  
sds@gulf-marine.com

### 1.4. Emergency telephone number

Emergency telephone: Tel: +852 36930568

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

GHS: The product is not classified.

### 2.2. Label elements

Safety data sheet available on request.

### 2.3. Other hazards

Other: Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne. The harmful effects may increase in used oil.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Mineral oil and additives.

Only classified substances above threshold limits are shown.

GHS:

%:	CAS-No.:	EC No.:	REACH Reg. No:	Chemical name:	Hazard classification:	Notes:
0.1-<1	900185-23-1	-	-	Benzoic acid, hydroxy-, mono-C20-28-branched alkyl derivs., calcium salts (2:1)	Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 4;H413	

Notes: DMSO < 3% (IP 346)

Reference: The full text for all hazard statements is displayed in section 16.



Marine

# SAFETY DATA SHEET

Product name:	GulfSea Power MDO 3012, 4012	Page:	2/8
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

---

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

Inhalation: Move into fresh air and keep at rest. In case of persistent throat irritation or coughing: Seek medical attention and bring these instructions.

Skin contact: Remove contaminated clothing. Rinse skin immediately. Thoroughly rub with liquid soap and wash with lukewarm water. Get medical attention if any discomfort continues.

Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

Ingestion: DO NOT induce vomiting. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

### 4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: If there is any suspicion of aspiration into the lungs either directly or as a result of vomiting, obtain medical advice.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Extinguishing media: Extinguish with foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards: When heated and in case of fire, harmful vapours/gases may be formed. Fire in closed areas should only be extinguished by trained personnel.

### 5.3. Advice for firefighters

Protective equipment for fire- fighters: Wear suitable respiratory protective equipment.

---



Marine

# SAFETY DATA SHEET

Product name:	GulfSea Power MDO 3012, 4012	Page:	3/8
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions: Mark the spillage. Avoid inhalation of oil mist and contact with skin and eyes. Keep public away from danger area. In case of spills, beware of slippery floors and surfaces.

Protective equipment: Wear necessary protective equipment.

### **6.2. Environmental precautions**

Environmental precautions: Avoid discharge into drains. Contact local authorities in case of spillage to drain/aquatic environment.

### **6.3. Methods and material for containment and cleaning up**

Methods for cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material.

### **6.4. Reference to other sections**

Reference: For personal protection, see section 8. For waste disposal, see section 13.

## SECTION 7: HANDLING AND STORAGE

### **7.1. Precautions for safe handling**

Safe handling advice: Observe good chemical hygiene practices. Avoid inhalation of oil mist and contact with skin and eyes. Avoid prolonged and repeated contact with oil, particularly used oil. Wash hands before breaks and before smoking, eating or drinking.

Technical measures: Use work methods which minimise oil mist production. Do not smoke or use open fire or other sources of ignition.

Technical precautions: When working with heated oil, mechanical ventilation may be required.

### **7.2. Conditions for safe storage, including any incompatibilities**

Technical measures for safe storage: Store in tightly closed original container in a well-ventilated place.

Storage conditions: Keep at a temperature not exceeding: 45°C.

### **7.3. Specific end use(s)**

Specific use(s): Lubricant.

---



Marine

# SAFETY DATA SHEET

Product name: GulfSea Power MDO 3012, 4012 Page: 4/8  
Supersedes date: 2019-11-18 Revision: 2019-11-18  
Product No.: SDS-ID: HK-EN/1.0

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>	<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
-	Oil mist, -mineral	-	5 mg/m3	PEL (Long Term)	-	
		-	10 mg/m3	PEL (Short Term)	-	

### 8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapours and oil mist.

Respiratory equipment: In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P3) can be used.

Hand protection: Gloves (synthetic rubber, neoprene)

Eye protection: Wear approved, tight fitting safety glasses where splashing is probable.

Skin protection: Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures: Wash hands after handling. Observe good chemical hygiene practices. Wash contaminated clothing before reuse. When using do not eat, drink or smoke. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

---



Marine

# SAFETY DATA SHEET

Product name: GulfSea Power MDO 3012, 4012  
Supersedes date: 2019-11-18  
Product No.:

Page: 5/8  
Revision: 2019-11-18  
SDS-ID: HK-EN/1.0

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance: Liquid.  
Colour: Amber.  
Odour: Mild.  
Odour threshold: Not available.  
pH: Not applicable.  
Melting point / freezing point: Not available.  
Boiling point: Not available.  
Flash point: >215°C  
ASTM D 92  
Evaporation rate: Not available.  
Flammability (solid, gas): Not applicable.  
Explosion limits: Not available.  
Vapour pressure: Not available.  
Vapour density: Not available.  
Relative density: 0.889 - 0.896 (15°C)  
Solubility: Soluble in: Organic solvents.  
Partition coefficient (n-octanol/water): Not available.  
Auto-ignition temperature (°C): Not available.  
Decomposition temperature (°C): Not available.  
Viscosity: 10.9 – 14.5 mm<sup>2</sup>/s (100°C)  
Explosive properties: Not available.  
Oxidising properties: Not available.

### 9.2. Other information

Other data: Pour point (°C): -18



Marine

# SAFETY DATA SHEET

Product name:	GulfSea Power MDO 3012, 4012	Page:	6/8
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

---

## SECTION 10: STABILITY AND REACTIVITY

### **10.1. Reactivity**

Reactivity: Not reactive.

### **10.2. Chemical stability**

Stability: Stable under normal temperature conditions.

### **10.3. Possibility of hazardous reactions**

Hazardous reactions: None known.

### **10.4. Conditions to avoid**

Conditions/materials to avoid: Heat, sparks, flames. Extremely high or low temperatures.

### **10.5. Incompatible materials**

Incompatible materials: Strong oxidizing substances.

### **10.6. Hazardous decomposition products**

Hazardous decomposition products: None under normal conditions. Hazardous polymerisation will not occur.

## SECTION 11: TOXICOLOGICAL INFORMATION

### **11.1. Information on toxicological effects**

Inhalation: Inhalation of oil mist or vapours formed during heating of the product may irritate the respiratory system and provoke throat irritation and coughing.

Skin contact: Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.

Eye contact: May cause temporary eye irritation.

Ingestion: Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis.

Specific effects: Used oil may contain harmful contaminants. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals.

---



Marine

# SAFETY DATA SHEET

Product name:	GulfSea Power MDO 3012, 4012	Page:	7/8
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

---

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecotoxicity: Not classified as dangerous to the environment.

### 12.2. Persistence and degradability

Degradability: Potentially degradable, but will persist in the environment for long periods.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

### 12.4. Mobility in soil

Mobility: Spillages may penetrate the soil causing ground water contamination.

### 12.5. Results of PBT and vPvB assessment

PBT/vPvB: Not known.

### 12.6. Other adverse effects

Other adverse effects: Not known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Waste is classified as hazardous waste. Dispose of waste and residues in accordance with local authority requirements.

Contaminated packaging: Disposal through approved facilities is recommended.

## SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

UN-No: Not regulated.

### 14.2. UN proper shipping name

Proper Shipping Name: Not regulated.

### 14.3. Transport hazard class(es)

Class: Not regulated.

### 14.4. Packing group

PG: Not regulated.

### 14.5. Environmental hazards

Marine pollutant: Not regulated.

### 14.6. Special precautions for user

Special precautions: Not regulated.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not regulated.

---



Marine

# SAFETY DATA SHEET

Product name:	GulfSea Power MDO 3012, 4012	Page:	8/8
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

---

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: Singapore Standard SS 586: Part 2 : 2014; Globally harmonised system of classification and labelling of chemicals - Singapore's adaptations. Guidelines on prevention and control of chemical hazard. Singapore Standard SS 586: Part 3 : 2014; Preparation of safety data sheets (SDS).

## SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

### Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

### Wording of H-statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H413	May cause long lasting harmful effects to aquatic life.

---

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature.

---